

80% SINGLE STAGE GAS FURNACE

EASIER TO SELL

- 80% AFUE
- Flame roll-out sensors standard
- Category I venting
- Blocked vent switch
- Louvered door
- 24 VAC humidifier terminal
- Electronic air cleaner terminal
- N8MXL model California NOx approved
- Certified 2% or less leakage of nominal air conditioning CFM delivered when pressurized to 1-inch water gauge with all present air inlets, air outlets, and condensate drain port(s) sealed

TOUGHER

- ECM blower motor
- Adjustable heating blower OFF delay
- Factory set blower ON delay
- RPJ aluminized steel heat exchanger
- High temperature limit control prevents overheating
- Direct ignition with Silicon Nitride ignitor
- One piece prepainted steel cabinet

QUIETER

- In-shot burners

EASIER TO INSTALL AND SERVICE

- 33-1/3" (847mm) high, for ease of installation
- Innovative knobs for easy door removal and secure attachment
- Factory shipped for natural gas, with propane gas conversion kits available
- Four position – upflow/downflow/horizontal (left/right) installation
- Three position vent elbow capability
- Through the casing flue pipe for counterflow applications
- Common venting with other Category I appliances
- Masonry chimney adapter available
- Self diagnostics
- Slide out blower assembly

WARRANTY*

- 20 year heat exchanger limited warranty
- 10 year parts limited warranty with timely registration
- 5 year parts limited warranty if not registered within 90 days of original installation

* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Illustrations and photographs are only representative. Some Product models may vary.

WARNING

CARBON MONOXIDE POISONING AND FIRE HAZARD
 Failure to follow this warning could result in personal injury, death, and/or property damage.
 This furnace is not designed for use in recreation vehicles, manufactured (mobile) homes or outdoors.
 Failure to follow this warning could result in personal injury, death, and/or property damage.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.

UNIT PERFORMANCE DATA

| Model | Heating Input (MBTUH) | Efficiency AFUE | Cooling Capacity CFM range @ .5 in. w.c. (125 Pa) | Operating Dimensions Height x Width x Depth inches (millimeters) | Operating Weight lbs (kg) | Notes |
|---------------|-----------------------|-----------------|---|--|---------------------------|-------|
| N8MXL0451412A | 44,000 | 80% | 415-1080 | 33-1/3 x 14-3/16 x 29 (847 x 360 x 737) | 104 (47) | |
| N8MXL0701712A | 66,000 | 80% | 385-1005 | 33-1/3 x 17-1/2 x 29 (847 x 445 x 737) | 126 (57) | |
| N8MXL0701716A | 66,000 | 80% | 875-1435 | 33-1/3 x 17-1/2 x 29 (847 x 445 x 737) | 126 (57) | |
| N8MXL0901714A | 66,000 | 80% | 750-1210 | 33-1/3 x 17-1/2 x 29 (847 x 445 x 737) | 127 (58) | |
| N8MXL0902116A | 88,000 | 80% | 845-1445 | 33-1/3 x 21 x 29 (847 x 533 x 737) | 140 (64) | |
| N8MXL1102120A | 110,000 | 80% | 990-2040 | 33-1/3 x 21 x 29 (847 x 533 x 737) | 152 (69) | |
| N8MXL1352420A | 132,000 | 80% | 1025-1810 | 33-1/3 x 24-1/2 x 29 (847 x 622 x 737) | 163 (74) | |